

Supplies a full range of quality flexible duct products



GLV International (1995) Ltd.

Tel: +972 9 796 56 07 | Fax: +972 9 796 64 78
david@glv1995.com | www.glv1995.com



NEW
Revolutionary



**PATENTED
PRODUCT**

AF-960

Introducing the new and revolutionary semi-rigid aluminum flexible duct:

- ▶ Heavy-duty - reinforced with steel wire - crush, tear and puncture resistant
- ▶ Single layer of pure aluminum tape (60 to 120 micron)
- ▶ Exceptionally durable and flexible
- ▶ Easy to install
- ▶ High compact ratio minimizes storage space
- ▶ Suitable for a wide range of applications



The AF-960 is best for use in heating, ventilation and air-conditioning systems (HVAC); clothes dryer heat extraction; as well as other applications

Construction: single layer of aluminum tape formed into a semi-rigid flexible duct reinforced by a bronze-coated bead wire helix

Properties:	Operating temperature range: -30°C to +250°C Maximum air velocity: 30 m/s Maximum working pressure: +3000Pa
Certifications:	UL2158A / for clothes dryer ducts - Class 0 (zero flame spread, zero smoke developed) UL181 / Class 0 (zero flame spread, zero smoke developed) EN13501-1:2013 / Reaction to fire – A1-s1,d0
Available diameters:	80mm-508mm
Standard length:	80mm-315mm – up to 5m 356mm-508mm – up to 3m

